

Paragon Paints

Technical Data Sheet

Wheldrake Lane, Elvington, York, YO41 4AZ

Tel: 01904 607584

01/12/15

Product: Paragon Paints Brass Lacquer

Sizes Available: 500ml, 1 Litre & 2.5 Litre tins

Colours: Clear

Description: Paragon Paints clear acrylic brass lacquer dries to a tough, glossy coating. This lacquer has excellent adhesion properties together with good weathering properties, retaining colour, and prevents tarnishing. It is especially suitable for application to non ferrous metals such as copper, brass, bronze and aluminium.

Technical Information

Coverage: 10 Square metre per litre

Storage: 24 months in original sealed container

Cleaning: Thoroughly degrease surface using PT1 thinner. If necessary remove any oxide layer by light abrasion.

Health & Safety: Please refer to Paragon Paints Material Safety Data Sheet and to tin label prior to use.
Suitable respiratory equipment should be worn when spraying.

Application Methods

	Thinners	Coats	Touch Dry at 20°C	Hard Dry at 20°C	Firm Dry at 20°C
Brush:	None	1 – 2	40 Minutes	1 Hours	6 Hours
Spray:	10-15% Synthetic PT1	1 – 2	40 Minutes	1 Hours	6 Hours

Overcoat after 4 hours minimum

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or process. Such information is to the best of Paragon Paints knowledge and belief accurate and reliable as to the date indicated. However, no representation, warranty or guarantee is made as to its accuracy reliability or completeness. It is the users' responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use.