

Paragon Paints

Technical Data Sheet

Wheldrake Lane, Elvington, York, YO41 4AZ

Tel: 01904 607584

01/12/12

Product: Paragon Paints Coach Enamel **Sizes Available:** 500ml, 1 Litre, 2.5 Litre & 5 Litre tins **Colours:** Extensive range of colours

Description: Paragon Paints Coach Enamel is a traditional ultra high quality, high build, high solids, and alkyd synthetic enamel. It is formulated primarily for brushing but spray application will also produce excellent results. Paragon Paints Enamel offers ultimate gloss, build and scratch filling with an extra long wet edge time. It has excellent water resistance and flexibility with a good exterior durability and toughness.

Maximum VOC Content (RFU): 0.45kg/ltr **Regulations/Compliance:** Out of scope

Technical Information

Coverage: 12 Square metre per litre **Flashpoint:** Above 38°C **Temperature Resistance:** 170 Degrees C

Storage: 12 months in original sealed container

Cleaning: Ensure surfaces to be coated are dry and free of all traces of contaminants

Health & Safety: Please refer to Paragon Paints Material Safety Data Sheet and to tin label prior to use. Suitable respiratory equipment should be worn when spraying.

Application Methods

	Thinners	Coats	Touch Dry at 20°C	Hard Dry at 20°C	Firm Dry at 20°C
Brush:	None	2 – 3	2 Hours	12 Hours	24 Hours
Spray:	10-15% Synthetic PT8	2 – 3	2 Hours	6 Hours	12 Hours

Overcoat after 16 hours minimum

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or process. Such information is to the best of Paragon Paints knowledge and belief accurate and reliable as to the date indicated. However, no representation, warranty or guarantee is made as to its accuracy reliability or completeness. It is the users' responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use.