

Paragon Paints

Technical Data Sheet

Wheldrake Lane, Elvington, York, YO41 4AZ

Tel: 01904 607584

01/12/12

Product: Paragon Paints Single Pack Etch Primer **Sizes Available:** 500ml, 1 Litre, 2.5 Litre & 5 Litre tins **Colours:** Grey, White & Black

Description: Paragon Paints SP Etch Primer is a fast drying spray quality self-etching primer for application to steel and aluminum. It has good heat resistance up to approx 200 C. and can be over coated with a wide range of topcoats. Etch primers once they are touch dry can normally be recoated at any time. There is however a number of factors, such as film thickness, air temperature, air movement etc that can substantially alter the through dry time so we recommend doing a small test patch before over coating a large area

Regulations/Compliance: Out of scope

Technical Information

Coverage: 12 sqm per litre at 15 microns dry film thickness **Flashpoint:** 21 Degrees C **VOC(supplied)** 650-700 grams/litre

Storage: 12 months in original sealed container

Cleaning: Ensure surfaces to be coated are dry and free of all traces of contaminants

Health & Safety: Please refer to Paragon Paints Material Safety Data Sheet and to tin label prior to use. Suitable respiratory equipment should be worn when spraying.

Application Methods

	Thinners	Coats	Touch Dry at 20°C	Through Dry at 20°C
Brush:	PT3	2 – 3	20 Minutes	1 Hour
Spray:	10% Synthetic PT3	2 – 3	20 Minutes	1 Hour

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or process. Such information is to the best of Paragon Paints knowledge and belief accurate and reliable as to the date indicated. However, no representation, warranty or guarantee is made as to its accuracy reliability or completeness. It is the users' responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use.