

Paragon Paints

Technical Data Sheet

Wheldrake Lane, Elvington, York, YO41 4AZ

Tel: 01904 607584

01/12/12

Product: Paragon Ultra Clear Lacquer **Sizes Available:** 500ml, 1 Litre, 2.5 Litre tins.

Description: Paragon Ultra Clear Lacquer is a high temperature ultra clear UV resistant lacquer. Provides a crystal clear final lacquer coat for the highest quality finish.

Maximum VOC Content (RFU): 0.45kg/ltr **Regulations/Compliance:** Out of scope

Technical Information

Coverage: 12 Square metre per litre **Flashpoint:** Above 38°C **Temperature Resistance:** 170 Degrees C

Storage: 12 months in original sealed container

Cleaning: Ensure surfaces to be coated are dry and free of all traces of contaminants

Health & Safety: Please refer to Paragon Paints Material Safety Data Sheet and to tin label prior to use. Suitable respiratory equipment should be worn when spraying.

Application Methods

	Thinners	Coats	Touch Dry at 20°C	Hard Dry at 20°C	Firm Dry at 20°C
Brush:	None	2 – 3	2 Hours	12 Hours	24 Hours
Spray:	10-15% Synthetic PT8	2 – 3	2 Hours	6 Hours	12 Hours

Overcoat after 16 hours minimum

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or process. Such information is to the best of Paragon Paints knowledge and belief accurate and reliable as to the date indicated. However, no representation, warranty or guarantee is made as to its accuracy reliability or completeness. It is the users' responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use.