

# ZPG BRUSHING GREY PRIMER

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name:** ZPG BRUSHING PRIMER

**Product code:** ZPG

**Product description:** Air drying primer.

**CAS No.:** Not applicable.

**EC No.:** Not applicable.

**Index No.:** Not applicable.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified use(s):** Primer for brush application to metal.

**Uses advised against:** Follow supplier's recommendations on correct use of the product.

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Stationary Engine Parts Ltd  
T/A Paragon Paints  
Wheldrake Lane  
Elvington  
York  
North Yorkshire  
YO41 4AZ

**Telephone:** +44 (0)1904 607584

**E-mail:** info@paragonpaints.co.uk

### 1.4 Emergency telephone number

**In case of emergency, call:** +44 (0) 7774 460658 (UK number, 24 hours, 7 days)

## SECTION 2: Hazard Identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No. 1272/2008 (CLP)**

Flammable Liquid 3; H226

Specific Target Organ Toxicity Single Exposure 3; H336

Specific Target Organ Toxicity Repeated Exposure 2; H373  
Aspiration Toxicity 1, H304

## 2.2 Label elements according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



**Signal Word:** Danger

**Hazard Statement(s):**  
H226: Flammable liquid and vapour.  
H336: May cause drowsiness or dizziness.  
H373: May cause damage to organs through prolonged or repeated exposure if inhaled.  
H304: May be fatal if swallowed and enters airways.

**Precautionary Statement(s):**  
P210: Keep away from heat / sparks / open flames / hot surfaces. No smoking.  
P273: Avoid release to the environment.  
P260: Do not breathe vapours.  
P301 + P310: IF SWALLOWED: Immediately call a doctor/physician.  
P331: Do NOT induce vomiting.  
P501: Dispose of contents/container to hazardous waste.

**Supplemental Hazard information (EU):** EUH208: Contains Methyl ethyl ketoxime & Fatty acids, C6-19 branched, cobalt (2+) salts. May produce an allergic reaction.

EUH066: Repeated exposure may cause skin dryness or cracking.

**Contains:** White spirit

## 2.3 Other hazards:

Product may charge electrostatically.

# SECTION 3: Composition

## 3.2 Mixtures

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Chemical name	% w/w	CAS No.	EC No.	Index No.	Classification
Hydrocarbons, C9-11, n-alkanes, isoalkanes, cyclics, <2% aromatics  <i>REACH Registration no.: 01-2119463258-33</i>	4 - 26	-	919-857-5	-	Flam. Liq. 3; H226 STOT SE3; H336 Asp. Tox. 1; H304 EUH066
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, aromatics (2 - 25%)  <i>REACH Registration no.: 01-2119458049-33-xxxx</i>	3 - 5	64742-82-1	919-446-0	-	Flam. Liq. 3; H226 STOT SE3; H336 STOT RE1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066
Methyl ethyl ketoxime  <i>REACH Registration no.: 01-2119539477-28</i>	< 0.3	96-29-7	202-496-6	616-014-00-0	Acute Tox. 4; H312 Eye Dam. 1; H318 Skin Sens. 1; H317 Carc. 2; H351
Hexanoic acid, 2-ethyl-, zirconium salt  <i>REACH Registration no.: 01-2119979088-21</i>	< 0.2	22464-99-9	245-018-1	-	Repr. 2; H361
Fatty acids, C6-19 branched, cobalt (2+) salts	< 0.2	68409-81-4	270-066-5	-	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Repr. 2; H361 Aquatic Chronic 2; H411

See Section 16 for full description of H statements.

## SECTION 4: First Aid Measures

### 4.1 Description of first aid measures

**INHALATION:**

Remove patient to fresh air and keep at rest. If there are breathing problems, seek medical advice.

**SKIN CONTACT:**

Remove contaminated clothing immediately. Rinse skin with water or shower and wash with soap and water. Seek medical advice if symptoms persist.

**EYE CONTACT:**

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical advice if irritation persists.

**INGESTION:**

Give small quantities of water to drink. Do NOT induce vomiting. Obtain immediate medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness. May produce an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.

#### **4.3 Indication of any immediate medical attention and special treatments needed**

If ingested, product may be aspirated into the lungs and cause chemical pneumonitis. Treat symptomatically.

## **SECTION 5: Fire-fighting Measures**

### **5.1 Extinguishing Media**

**Suitable extinguishing media:** Foam, CO<sub>2</sub> or dry powder.

**Unsuitable extinguishing media:** Do not use water jet.

### **5.2 Special hazards arising from the substance or mixture**

Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back, causing fire or explosion. Containers may rupture on heating. Toxic gases may be formed in a fire.

### **5.3 Advice for fire-fighters**

FLAMMABLE. Evacuate area. Prevent run-off from fire control or dilution from entering drains or water courses. Self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire-exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses.

Flash point: 40 °C.

## **SECTION 6: Accidental Release Measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Avoid inhalation of vapours. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate (see Section 8).

#### **6.1.2 For emergency responders**

Keep unnecessary personnel away. Wear suitable protective clothing (see Section 8). Contaminated clothing should be thoroughly cleaned.

### **6.2 Environmental precautions**

Collect spillage. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

### **6.3 Methods and materials for containment and clearing up**

### **6.3.1 For containment**

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable adsorbent material.

### **6.3.2 For cleaning up**

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools transfer the contaminated adsorbent material into sealable containers for disposal. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

### **6.3.3 Other advice**

None

## **6.4 Reference to other sections**

See Section 8 for personal protective equipment. See Section 13 for waste disposal.

# **SECTION 7: Handling and Storage**

## **7.1 Precautions for safe handling**

Provide adequate ventilation, including local extraction to ensure the occupational exposure limit is not exceeded. Do not inhale vapours. Avoid contact with skin and eyes. Wear suitable personal protective equipment (see Section 8). Eliminate all sources of ignition. Electrical equipment should be protected to the appropriate standard.

Do not eat, drink or smoke when using this product. Wash exposed skin after use. Contaminated work clothing should not be allowed out of the workplace. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

## **7.2 Conditions for safe storage, including any incompatibilities**

Keep away from heat and sources of ignition. Keep from direct sunlight. Store locked up. Store only in the original container. Do not pressurise container. Product may charge electrostatically so all containers and associated equipment should be earthed and bonded to prevent static charge accumulation. Store in a cool, well ventilated place. Empty containers retain product residue and can be hazardous.

Ensure compliance with all regulations and guidance associated with the storage and use of flammable liquids.

See section 10 for incompatible materials.

## **7.3 Specific end uses(s)**

Primer for brush application to metal.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Workplace exposure limits (WEL) – United Kingdom

Source: EH40/2005, 2<sup>nd</sup> Ed., 2011

Substance	CAS no.	LTEL (8 hr TWA)		STEL (15 min)	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
White spirit	64742-82-1	-	350		

#### Other exposure limits

Consult applicable national legislation for WELs in other countries.

#### Biological limits

None assigned.

#### Derived No-Effect Level (DNEL) - industry

Substance	Dermal	Inhalation	Oral
White spirit	Long-term: 44 mg/kg/day – systemic effects	Long-term: 330 mg/m <sup>3</sup> – systemic effects	Not available

#### Derived No-Effect Level (DNEL) - consumer

Substance	Dermal	Inhalation	Oral
White spirit	Long-term: 26 mg/kg/day – systemic effects	Long-term: 71 mg/m <sup>3</sup> – systemic effects	Long-term: 26 mg/kg/day – systemic effects

#### Predicted No-Effect Concentration (PNEC)

Not available.

### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction. Electrical equipment should be protected to the appropriate standard.

<b>8.2.2 Personal protection:</b>	A suitable and sufficient COSHH assessment must be undertaken and appropriate and compliant personal protective equipment (PPE) provided and used.
<b>Eye protection:</b>	Goggles or glasses.
<b>Skin protection:</b>	Appropriate barrier creams.
<b>Hand protection:</b>	Chemical resistant gloves. (EN 374).
<b>Other:</b>	Long sleeve protective clothing. Plastic apron. Rubber boots.
<b>Respiratory protection:</b>	In the case of insufficient ventilation, wear suitable respiratory equipment.

### 8.2.3 Environmental exposure controls

Inform environmental manager of all incidents involving this product.

## SECTION 9: Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Grey viscous liquid
<b>Odour:</b>	Solvent
<b>Odour threshold:</b>	Not available
<b>pH:</b>	Not applicable
<b>Melting/freezing point:</b>	Not available
<b>Initial boiling point and boiling range:</b>	Not available
<b>Flash point:</b>	40°C (closed cup)
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid; gas):</b>	Not applicable
<b>Upper/lower flammability or explosive limits:</b>	Not available
<b>Vapour pressure:</b>	Not available.
<b>Vapour density:</b>	Not available
<b>Relative density:</b>	1.2 to 1.4 (Water = 1)
<b>Solubility:</b>	Insoluble in water
<b>Partition coefficient: n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	8 to 9 poise (ICI rotothinner, 20°C)
<b>Explosive properties:</b>	Vapour may form explosive mixture with air
<b>Oxidising properties:</b>	Not oxidising

### 9.2 Other information

None

## **SECTION 10: Stability and Reactivity**

<b>10.1 Reactivity</b>	Reacts with strong oxidising agents.
<b>10.2 Chemical stability</b>	Stable under normal conditions.
<b>10.3 Possibility of hazardous reactions</b>	No hazardous reactions expected during normal use.
<b>10.4 Conditions to avoid</b>	Keep away from sources of ignition, hot surfaces, direct sunlight and other sources of ignition.
<b>10.5 Incompatible materials</b>	Strong oxidising agents.
<b>10.6 Hazardous decomposition products</b>	Combustion may liberate toxic smoke, fumes, incomplete combustion products and oxides of carbon.

## **SECTION 11: Toxicological Information**

### **11.1 Information on toxicological effects**

<b>Acute toxicity</b>	Low acute toxicity.
<b>Skin corrosion/irritation</b>	Repeated exposure may cause skin dryness or cracking.
<b>Serious eye damage/irritation</b>	Not irritating to eyes.
<b>Skin sensitisation</b>	May produce an allergic skin reaction.
<b>Respiratory irritation</b>	Vapour irritates the nose, throat and lungs.
<b>Respiratory sensitisation</b>	No evidence of respiratory sensitisation.
<b>Germ cell mutagenicity</b>	Not mutagenic.
<b>Carcinogenicity</b>	Not classified. The product does not contain substances classified as carcinogenic above the classification thresholds.
<b>Reproductive toxicity</b>	Not classified. The product does not contain substances classified for reproductive toxicity above the classification thresholds.
<b>Specific Target Organ Toxicity – single exposure</b>	Inhalation of high concentrations of vapour may cause drowsiness or dizziness.
<b>Specific Target Organ Toxicity – repeated exposure</b>	Prolonged or repeated inhalation of high concentrations of vapour may cause organ damage.
<b>Aspiration hazard</b>	If ingested, may be aspirated into the lungs and cause chemical pneumonitis.



## Information on likely routes of exposure

Inhalation	See above
Skin contact	See above
Eye contact	See above
Ingestion	See above

**Symptoms related to the physical, chemical and toxicological characteristics** See above

**Other information** None

## SECTION 12: Ecological Information

<b>12.1 Toxicity</b>	The product is low hazard for the environment.  The following data is for White spirit:  LC50 96h fish: < 30 mg/l ( <i>Onchorhynchus mykiss</i> ) EC50 48h aquatic invertebrates: < 22 mg/l ( <i>Daphnia magna</i> ) EC50 72h aquatic plants: < 10 mg/l EC50 48h microorganisms: 44 mg/l NOEC 21d aquatic invertebrates: 0.097 mg/l ( <i>Daphnia magna</i> )
<b>12.2 Persistence and degradability</b>	Data for White spirit: Readily biodegradable - 75% in 28 days.
<b>12.3 Bioaccumulative potential</b>	Not applicable.
<b>12.4 Mobility in soil</b>	Not applicable.
<b>12.5 Results of PBT and vPvB assessment</b>	Not classified as PBT/vPvB by current EU criteria.
<b>12.6 Other adverse effects</b>	No other adverse effects are expected.

## SECTION 13: Disposal Considerations

### 13.1 Waste treatment methods

Product and packaging to be disposed of as hazardous waste. Disposal should be in accordance with local, state or national legislation.

Contaminated adsorbent must be removed in sealed drums and disposed of via an authorised waste disposal contractor. Do not empty into drains; dispose of this material and its container in a safe way.

Empty containers may contain residue and may be dangerous. Do not attempt to refill or clean containers without proper instructions. Do not pressurise, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity or other sources of ignition. Residual flammable vapour may cause an explosion.

## **SECTION 14: Transport Information**

### **ROAD (ADR)**

<b>14.1 UN Number</b>	1263
<b>14.2 UN Proper shipping name</b>	PAINT
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	III
<b>14.5 Environmental hazards</b>	No

### **INLAND WATERWAYS (ADN/ADNR)**

<b>14.1 UN Number</b>	1263
<b>14.2 UN Proper shipping name</b>	PAINT
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	III
<b>14.5 Environmental hazards</b>	No

### **RAIL (RID)**

<b>14.1 UN Number</b>	1263
<b>14.2 UN Proper shipping name</b>	PAINT
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	III
<b>14.5 Environmental hazards</b>	No

### **AIR (IATA/ICAO)**

<b>14.1 UN Number</b>	1263
<b>14.2 UN Proper shipping name</b>	PAINT
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	III
<b>14.5 Environmental hazards</b>	No

### **SEA (IMDG)**

<b>14.1 UN Number</b>	1263
<b>14.2 UN Proper shipping name</b>	PAINT
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	III
<b>14.5 Environmental hazards</b>	No
<b>14.6 Transport in bulk according to Annex II</b>	

## SECTION 15: Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP).

### 15.2 Chemical Safety Assessment

Not applicable.

## SECTION 16: Other Information

### Full text of relevant H-statements:

H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H351: Suspected of causing cancer.  
H361: Suspected of damaging fertility or the unborn child.  
H372: Causes damage to organs through prolonged or repeated exposure.  
H411: Toxic to aquatic life with long lasting effects.

### References:

Suppliers' Safety Data Sheets for components  
Regulation (EC) No. 1272/2008  
EH40/2005, 2<sup>nd</sup> Ed., 2011

### Disclaimer:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE, BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM, IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

### Version history:

Version:	1.0
Issue date:	31/12/2016
Previous Version:	Not numbered
Issue date of previous version:	14/03/98

**Sections changed from previous version:**

All sections reviewed and revised